



TYPICAL SETUP




OPTION: REMOTE LOCATION OF HEAD UNIT




NOTE:

- ① INTERMEDIATE CYLINDER IS CUSTOM MADE AS FLOOR THICKNESS MAY VARY FROM HOME TO HOME.
- ② INTERMEDIATE CYLINDER IS CUSTOM MADE AS ROOM HEIGHT MAY VARY FROM HOME TO HOME.
- ③ MINIMUM ALLOWABLE HEIGHT IS 2340mm
- ④ MINIMUM ALLOWABLE HEIGHT AS SHOWN FOR THIS TYPE OF INSTALLATION
- ⑤ INTERNAL DIAMETER OF CABIN WITHOUT THE COLUMNS IS 820mm AND THE INTERNAL CABIN HEIGHT IS 2007mm
- ⑥ DOOR WIDTH IS 521mm
- ⑦ MAX. ELEVATOR HEIGHT IS 10m

VIEW "A-A"
SCALE: 2:1



DETAIL "A"
SCALE: 2:1
(TYPICAL OF FLOOR PENETRATION)



Information contain herein is the property of Pneumatic Vacuum Elevators LLC. No reproduction or disclosure of this information may be made by the recipient to any person or organization without the written consent of Pneumatic Vacuum Elevators LLC.

Itemref.	Quantity	Material	Dimensions		Article No./ Reference		
PNEUMATIC VACUUM ELEVATORS LLC			TYPICAL PVE37 HOME INSTALLATION FOR A 2STOP ELEVATOR				
			Designed by HS	Scale 1:1	Drawing No. D-TYP-H-01	Rev 1	Date 12/20/12